

# UTILITY/SPECIALTY AG TRACTORS



## Narrow Models

M4N-071 | M5N-091PK | M5N-091/111 Cab | M5N-111  
M5N-092/112 Open Station

## Capable. Compact. Nimble.

- › Narrow models (M4N-071 | M5N-091PK | M5N-091/111 Cab | M5N-111 | M5N-092/112 Open Station) measure just 48" outside to outside at rear axle with standard tires
- › The 4WD M5N-091PK (Power Krawler), with its powerful engine and independently oscillating left and right rear tracks, provides excellent traction and sure-footed climbing in vineyards and other hilly terrain
- › Electro-hydraulic Shuttle Transmission is standard on all M Series models and makes shifting between forward and reverse a smooth and quick operation
- › Bevel Gear Front Wheel Drive with Bi-Speed Turn on the M Series narrow tractors delivers strength, maneuverability, and durability
- › Automatic 4WD braking on all M4N/M5N models from 2WD mode
- › The M4N and M5N have a V-3800 Tier 4 engine, increased alternator capacity, larger radiator, larger diameter cooling fan, and RPM memory for repetitious actions compared to previous models
- › To promote operator efficiency, all main controls are on the right-hand side of the operator while the steering wheel now has up to 25 degrees of tilt
- › Tracks offer an alternative to keep the narrow profile of the tractor while in the field



# UTILITY/SPECIALTY AG TRACTORS

## Narrow Models

	<b>M4N-071 HD12 / HDC12</b>	<b>M5N-091PK Power Krawler</b>	<b>M5N-091HDC12 M5N-091HDC24 M5N-092HD12 M5N-092HD24</b>	<b>M5N-111HDC12 M5N-111HDC24 M5N-112HD12 M5N-112HD24</b>
<b>Engine Type (Kubota, liquid-cooled, diesel)</b>	CRS, Direct Injection, 4-cylinder, turbocharged, Tier 4	CRS, Direct Injection, 4-cylinder, turbocharged w/ intercooler, Tier 4		
<b>Horsepower (gross)*</b>	72.6	92.5		105.7
<b>Horsepower (PTO)**</b>	61	78	<b>HD(C)12: 78 HD(C)24: 75</b>	<b>HD(C)12: 91 HD(C)24: 88</b>
<b>Displacement (cu. in.)</b>	230			
<b>Alternator (amps)</b>	100 (130 opt. on cab model)	80 (130 opt. on cab models)		
<b>Transmission (fully synchronized)</b>	F12/R12 (F18/R18 w/creep)		<b>HD(C)12:</b> F12/R12 (F18/R18 w/creep) / <b>HD(C)24:</b> F24/R24 (F36/R36 w/creep)	
<b>Height (top of hood / cab)</b>	54.7" / 90.2"	N/A / 93.3"	59.8" / 90.2"	
<b>Overall Width (ROPS / cab)</b>	51.6" / 53.9"	N/A / 48"	53.5" / 53.9"	
<b>Overall Length</b>	147.6" / 149.2"		155.5"	
<b>Crop Clearance (front axle)</b>	12" (ROPS) / 14.6" (cab)			
<b>Wheelbase</b>	83.9"			
<b>Tractor Weight (ROPS/cab) (lbs.)</b>	5,049 / 5,291	N/A / 7,275	5,357 / 5,622	

\* SAE J1995; \*\* OECD Code 2

