

# Specifications

Model		GR2020G	GR2120
<b>Engine</b>			
Model		GH631	D782
Type		2 cylinders, gasoline, air cooled	3 cylinders, diesel, water-cooled
Total displacement	cu.in. (cc)	41.1 (674)	47.5 (778)
Gross horsepower*	HP (kW)	20.5 (15.3)	17.0 (12.7)
Engine layout		Horizontal	
Fuel tank capacity	gal. (ℓ)	4.2 (16)	4.8 (18)
<b>Dimension</b>			
Overall length	in. (mm)	78.3 (1990)	
Overall width (with 48" / 54" mower deck)	in. (mm)	61.0 (1550) / –	61.0 (1550) / 66.9 (1700)
Overall height	in. (mm)	50.8 (1290)	
Wheelbase	in. (mm)	50.4 (1280)	
Ground clearance (with 48" / 54" mower deck)	in. (mm)	4.7 (120)	
<b>Tread</b>			
Front/Rear	in. (mm)	32.5 (825) / 32.2 (820)	
<b>Weight</b> (with 48" / 54" mower deck)	lbs. (kg)	882 (400) / –	959 (435) / 970 (440)
<b>Tire size</b>			
Front/Rear		16 × 7.5–8 / 23 × 10.50–12	
<b>Transmission</b>		Hydrostatic transmission	
<b>Transmission drive</b>		Shaft drive	
<b>Speed control</b>		Single foot pedal	
<b>Traveling speed</b>			
Forward/Reverse	mph (km/h)	0–6.2 (0–10.0) / 0–3.1 (0–5.0)	
<b>Cruise control</b>		Std.	
<b>Brake</b>		Internal expanding brake	
<b>PTO clutch</b>		Hydraulic wet multi discs	
<b>Mower deck drive</b>		Shaft drive	
<b>Steering system</b>		Glide Steer, hydraulic power steering	
<b>Operator's deck</b>		Flat	
<b>Seat adjustment</b>		Slide	
<b>Seat suspension</b>		Mechanical suspension with weight adjustment	
<b>Fuel gauge</b>		Std.	
<b>Hour meter</b>		Std.	
<b>Easy checker</b>		Std.	
<b>Mower OPC.</b>		Std.	
<b>Travel OPC.</b>		Std.	
<b>Blade shut off brake</b>		PTO Clutch	
<b>Grass catcher (optional)</b>			
Capacity	bushel	10	
Material of bag		cloth	

## Mower Specifications

Model		RCK48GR	RCK48GR / RCK54GR
<b>Cutting width</b>	in. (mm)	48 (1219)	48 (1219) / 54 (1372)
<b>Lifting device</b>		Hydraulic	
<b>Mower mounting method</b>		Parallel linkage	
<b>Cutting height</b>	in. (mm)	1.0–4.0 (25–102)	
<b>Cutting height adjustment</b>		Dial gauge	
<b>Cutting height increments</b>		1/4"	
<b>Number of blades</b>		3	
<b>Direction of discharge</b>		Right side	
<b>Minimum uncut diameter</b>	in. (mm)	43 (1100)	43 (1100) / 35 (900)

\* Power(HP) specifications for individual gasoline/diesel engine models are rated pursuant to Society of Automobile Engineers(SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [kubotaUSA.com](http://kubotaUSA.com)

©2019 Kubota Corporation