

Front Loader Specifications

Model		LM2605	
Leveling system		Kubota Z-bar linkage, mechanical self-leveling (MSL)	
Attachment		96 in. Bucket	
Compatibility		for M7 Standard models (Pressure Compensated, Fixed Displacement hydraulics)	for M7 Premium and Premium KVT models (Closed center hydraulics)
Control type		Mechanical lever	Electrial joy stick
Max. lifting height at bucket pivot pin	in. (mm)	167 (4250)	
Max. lifting height at bucket under level	in. (mm)	156 (3972)	
Clearance with bucket dumped	in. (mm)	131 (3321)	
Max. dumping angle	degree	59	
Max. roll-back angle	degree	42	
Digging depth	in. (mm)	3.9 (100)	
Lifting capacity at bucket pivot pin, max. height	lbs (kg)	5776 (2620)	
Lifting capacity at 800mm forward, max. height	lbs (kg)	5765 (2615)	
Breakout force at bucket pivot pin	lbs (N)	9069 (40342)	
Breakout force at 800mm forward	lbs (N)	7968 (35444)	
Bucket roll-back force at max. height	lbs (N)	5972 (26566)	
Bucket roll-back force at 59in.(1.5M) height	lbs (N)	11017 (49004)	
Bucket roll-back force at ground level	lbs (N)	10825 (48151)	
Raising time	sec.	6.4	5.4
Lowering time	sec.	8.1	8.1
Bucket dumping time	sec.	5.1	5.1
Bucket rollback time	sec.	4.6	4.6
Standard equipment		Third function valve, Single-lever hydraulic valve quick coupler, Accumulator (KSR: Kubota Shockless Ride)	

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.