

## SPECIFICATIONS

MODEL	M4D-061HDC12		M4-071HDC12		M4D-071HDC12	
	4WD		4WD		4WD	
<b>CAB</b>	Ultra Grand Cab II		Ultra Grand Cab II		Ultra Grand Cab II	
<b>ENGINE</b>	<b>V3307-CR-TE4</b>					
<b>Type (Make: Kubota)</b>	4 cylinder in-line, Common Rail System, Direct Injection					
<b>No. of Cylinders /Aspiration</b>	4 / turbocharged					
<b>Engine Net Power*</b>	HP (kW)	65.4 (48.8)			73.2 (54.6)	
<b>PTO Power</b>	HP (kW)	52 (38.8)			60 (44.7)	
<b>Total Displacement</b>	cu.in. (cc)	203 (3331)				
<b>Rated Engine RPM</b>	ROPS/CAB	2400				
<b>Fuel Tank Capacity</b>	ROPS/CAB gal. (L)	23.8 (90)				
<b>Alternator</b>	Amp	130				
<b>TRANSMISSION</b>						
<b>No. of Speeds</b>	F12 / R12 (option: F18 / R18 with Creep)					
<b>Main Gear Shift</b>	Fully synchronized (6 speed)					
<b>Shuttle Shift</b>	Electro Hydraulic Shuttle					
<b>Main Clutch Type</b>	Multiple wet disc					
<b>Brake Type</b>	Hydraulic wet disc					
<b>Differential Lock (Front / Rear)</b>	Limited Slip Differential / Mechanical					
<b>4WD Clutch Type</b>		Electro-hydraulic on-the-go	Mechanical on-the-go		Electro-hydraulic on-the-go	
<b>PTO</b>						
<b>Type</b>	Live-independent PTO, electro-hydraulic clutch with brake					
<b>Speed</b>	RPM	540 / 540E	540 (540 / 540E: OPT)		540 / 540E	
<b>HYDRAULICS</b>						
<b>Pump Capacity (3-Point Hitch)</b>	gpm ( /min.)	16.7 (63.3)				
<b>3-Point Hitch</b>	Telescopic lower link ends, Telescopic Stabilizers					
<b>Category</b>	I / II					
<b>Control System</b>	Position, draft (top link sensing) & mixed control					
<b>Lift Capacity at 24 in. behind Lift Point (ASAE)</b>	lbs. (kg)	3307 (1500)				
<b>Cylinder Type</b>	Two external cylinders					
<b>No. of Standard Remote Valves</b>		2 (SCD / FD), Max. 3	1 (SCD), Max. 3		2 (SCD / FD), Max. 3	

## SPECIFICATIONS

MODEL	M4D-061HDC12		M4-071HDC12		M4D-071HDC12	
	4WD		4WD		4WD	
<b>OTHER FEATURES</b>						
<b>4WD System</b>	Bevel gear type					
<b>Steering</b>	Hydrostatic power steering					
<b>Tilt Steering</b>	Standard					
<b>Hood Type / Pedal Type</b>	Full open, slanted, steel / Hanging					
<b>Deck Type (ISO-mounted w/rubber mat)</b>	Full-flat					
<b>Panel Type</b>	Electronic					
<b>STANDARD TIRE SIZE</b>						
<b>Front</b>	320 / 70R24					
<b>Rear</b>	420 / 75R34					
<b>DIMENSIONS &amp; WEIGHT</b>						
<b>Overall Length</b>		in. (mm)	142 (3600)			
<b>Overall Height</b>	Top of CAB	in. (mm)	101 (2560)			
<b>Overall Width (minimum)</b>		in. (mm)	75.6 (1920)			
<b>Wheelbase</b>		in. (mm)	84.1 (2135)			
<b>Crop Clearance (Front axle)</b>		in. (mm)	18.1 (460)			
<b>Tread Width</b>	Front	in. (mm)	58.5 (1487)			
	Rear	in. (mm)	56.2, 68.7 (1430, 1744)			
<b>Turning Radius (w/o brake)</b>		ft. (m)	11.8 (3.6)			
<b>Tractor Weight</b>		lbs. (kg)	6008 (2725)	5952 (2700)	6008 (2725)	



\*SAE J1349

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.