

SPECIFICATIONS

MODEL		BX1880	BX2380	BX2680	BX23S
ENGINE					
Type		Liquid-cooled, 3-cylinder diesel			
Model		Kubota D722	Kubota D902	Kubota D1005	Kubota D902
Engine Gross HP at 3200 RPM¹	<i>HP (kW)</i>	16.6 (12A)	21.6 (16.1)	24.8 (18.5)	21.6 (16.1)
PTO Horsepower at 3200 RPM	<i>HP (kW)</i>	13.7 (0.2)	17.7 (13.2)	19.5 (14.5)	17.7 (13.2)
Displacement	<i>cu.in. (cc)</i>	43.9(719)	54.8 (898)	61.1 (1001)	54.8 (898)
Fuel Tank Capacity	<i>gal (ℓ)</i>	6.6 (25)			
DRIVE TRAIN					
Transmission		HST, High-Low gear shift (2 forward/reverse)			
Drive Method		4WD			
Brakes		Wet disc			
PTO		Live independent PTO (with hydraulic clutch)			
Rear		STD (540RPM)			
Mid		STD (2500RPM)			
HYDRAULICS					
Pump Output	<i>gpm (ℓ/min.)</i>	6.2 (23.5)			
3-Point Hitch		SAE Category I			Optional
Lift Capacity at 24 in. Behind Pin	<i>lbs. (kg)</i>	680 (310)			
Steering		Hydrostatic Power Steering			

MODEL		BX1880	BX2380	BX2680	BX23S
TIRE SIZE					
Front	<i>Turf/Bar/Industrial</i>	16x7.5-8 / 16x7.5-8 / N.A.	18x8.5-10 / 18x8.5-10 / 18x8.5-10		18x8.5-10 / N.A. / 18x8.5-10
Rear	<i>Turf/Bar/Industrial</i>	24x12-12 / 24x12-12 / N.A.	26x12-12 / 26x12-12 / 26x12-12		26x12-12 / N.A. / 26x12-12
TRAVELLING SPEEDS AT RATED ENGINE RPM (TURF)					
Forward	<i>mph (km/h)</i>	0-7.8 (0-12.5)		0-8.4 (0-13.5)	
Reverse	<i>mph (km/h)</i>	0-5.9 (0-9.5)		0-6.5 (0-10.)	
DIMENSIONS					
Length with 3-point hitch	<i>in. (mm)</i>	95.5 (2425)			99.0 (2515) w/ Front guard
Width	<i>in. (mm)</i>	44.1 (1120)	45.1 (1145)		
Height with ROPS	<i>in. (mm)</i>	81.9 (2080)	83.1 (2110)		86.2 (2190)
Wheelbase	<i>in. (mm)</i>	55.1 (1400)			
Ground Clearance (front axle)	<i>in. (mm)</i>	7.6 (193)	8.4 (213)	8.9 (225)	8.4 (213)
Tread	Front	<i>in. (mm)</i> 36.6 (930)			
	Rear	<i>in. (mm)</i> 32.2 (820)			
Turning Radius (w/o brake)	<i>ft. (m)</i>	7.5 (2.3)			
Tractor Weight with ROPS	<i>lbs. (kg)</i>	1336 (606)	1443 (650)	1521 (670)	1600 (725)* ²

¹SAEJ1995 ²w/ Frontguard, w/ control valve assy

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

