

Specifications

		Kubota					
Model		Z412KW-48	Z422KW-54	Z422KWT-60	Z452KWI-54	Z452KWTI-60	
Engine*	Kubota model name	GH7302V		GH7301V		GH730V	
	Engine manufacturer	Kawasaki (FS series)			Kawasaki (FT series)		
	Type	Carburated Air cooled 2 cylinders gasoline engine			EFI Air cooled V-twin vertical crank shaft gasoline engine		
	Engine gross power	HP**	22.0	24.0	26.0		
Total displacement	cu.in. (cc)	44.3 (726)					
Starting system		Key			Push button		
Dimensions	Overall length	in. (mm)	80.9 (2055)				
	Overall width	w/ mower in. (mm)	61.1 (1552)	67.3 (1710)	73.6 (1870)	73.6 (1870)	
		w/o mower in. (mm)	48.7 (1236)		54.2 (1376)	54.6 (1388)	
	Overall height	w/ ROPS (upright) in. (mm)	69.8 (1772)				
	w/o ROPS (folded) in. (mm)	49.8 (1265)					
Wheelbase		in. (mm)	49.4 (1255)				
Tread/Tire	Tread	Front in. (mm)	37.2 (944)				
		Rear in. (mm)	39.4 (1000)		42.1 (1070)	42.1 (1070)	
	Tire size	Front tire in. (mm)	13 x 6.5-6 Smooth pneumatic			13 x 6.5-6 Semi-pneumatic	
		Rear tire in. (mm)	24 x 9.5-14 Low profile tire	24 x 12-14 Low profile tire	24 x 9.5-14 Low profile tire	24 x 12-14 Low profile tire	
Weight (w/ mower)	lbs. (kg)	904 (410)	918 (416)	954 (433)	988 (448)		
Transmission		Hydro-Gear® Commercial ZT-3600® 2-HST w/ Gear reduction (Independent)					
Speed control		2 Hand levers					
Traveling speed range	Forward	mph (km/h)	0 – 10.0 (0 – 16.0)				
	Reverse	mph (km/h)	0 – 5.0 (0 – 8.0)				
Braking system		Cog style parking lock / Foot pedal					
PTO	Type	Belt drive					
	Clutch type	Electric clutch					
	PTO brake	Dry disc					
Mower deck	Model	RCK48P-400Z	RCK54P-400Z	RCK60P-400Z	RCK54P-400Z	RCK60P-400Z	
	Mower deck type	Side discharge					
	Mower lift system	Mechanical / Foot pedal (right front)					
	Deck depth	in. (mm)	5.0 (127)				
	Belt type	Single V-groove belt					
	Deck steel thickness	in. (mm)	0.135 (3.4)				
	Anti scalp roller	Rigid					
	Cutting width	in. (mm)	48 (1219)	54 (1372)	60 (1524)	54 (1372)	60 (1524)
	Number of blades	3 blades					
	Cutting height	in. (mm)	1.5 - 5.0 (38 - 127) with 0.25 inch increments				
	Mounting system	Parallel linkage					
Blade tip speed		18800	18700	18300	18700	18300	
Seat		22 inch high back seat with 3 inch stroke suspension and 4 inch slide adjustment					
Fuel tank capacity	Gal. (ℓ)	6.8 (25.7)					
Battery		U1 (12V, RC : 45min, CCA : 300, CA : 410)					
Generator capacity	Amp	15A					
Hour meter		Standard					
Fuel gauge		Sight window					
Spindles		1.25" shaft diameter with cast aluminum and sealed bearings					

*These Kawasaki engines have been tested in accordance with SAE J1995.
 **Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

Attachment & Optional Kits



- Mulching Kit
- LED Work Lights
- Operator Controlled Discharge Chute (OCDC)
- Maintenance Lift Kit
- Striping Kit



- 3 Bag Grass Catcher
- Canopy
- Spark Arrestor Kit



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2024 Kubota Corporation



For Earth, For Life
Kubota



KUBOTA ZERO-TURN MOWER Z400 Series Z412/Z422/Z452

Crafted for both residential and professional users, the Z400 delivers exceptional comfort and convenience, coupled with performance and durability you expect from Kubota.

